

DATASHEET - Ecart 6



DIMENSIONS and WEIGHT

Vehicle size	L = 800 mm	
	W = 600 mm	
	H = 500 mm	
Equipment	Lift platform	
	Plane size	L = 800 mm
		W = 600 mm
Stroke	60 mm	
Vehicle weight w/o batteries	95 kg	

PAYLOAD and REQUIREMENTS

Nominal payload 100% deliveries	300 kg
Maximum payload 30% deliveries	350 kg
Payload max size	L = 800 mm
	W = 600 mm
	H = 1.000 mm
Center of gravity footprint	L = 650 mm
	W = 530 mm
Center of gravity height	H = 700 mm
Min load frame clearance	W = 700 mm
	H = 515 mm

PERFORMANCE

Kinematics and Drive	Differential, bidirectional
Speed	0,1 m/s min
	1,0 m/s max
X, Y accuracy	+/- 10 mm
θ accuracy	+/- 1°
Localization rate	5 Hz
Minimum bending radius	0 m; the vehicle turns on its vertical axis
Slope	5% (2,9°)
Slope min bending radius	15 m
Step	±5 mm
Gap	10 mm
Motor wheel power	2x200 W
Braking torque	2x2 Nm

MATERIALS

Wheels coating	Polyurethane grip
Chassis material	AISI 304
Shell material	Painted Steel

BATTERY

Battery	LiFePO4 24V 50 Ah
Depth of discharge	70%
Autonomy	6 h
Recharging time	2 h
Battery weight	13 kg
Battery cycle life	2.000 cycles

COMMUNICATION

Communication	WI-FI - WLAN 802.11a/b/g/n - 2,4/5 GHz
---------------	--

SAFETY

Safety devices

- Nr. 2 Sick S300 laser scanners
- N.2 E-stop buttons
- Safety control central unit Sick Flexi

Performance Level

c

Safety field shape

Boxes: 360°
Trolleys: 180° front + 180° rear

NAVIGATION

Navigation	Odometric closed loop via laser scanner (natural navigation)
Mapping	Auto acquisition by Mobile Robot

ENVIRONMENT

Temperature	from +5 to 35 °C
Working relative humidity	from 30% to 80% (absence of condensation)
IP degree	13

REGULATIONS

Regulations	<ul style="list-style-type: none">• 2006/42/EC Machinery Directive
	<ul style="list-style-type: none">• 2014/35/EU Low Voltage Directive
	<ul style="list-style-type: none">• 2014/30/EU Electromagnetic Compatibility Directive
	<ul style="list-style-type: none">• ISO 3691-4: 2020 Safety of driverless industrial trucks