

DATASHEET - Ecabinet 2



DIMENSIONS and WEIGHT

Vehicle size	L = 800 mm
	W = 600 mm
	H = 1.235 mm

2-door cabinet double access

Equipment	Inside size	L = 610 mm
		W = 415 mm
		H = 840 mm

Lock Electric

Drawers size 600 x 400 mm

Vehicle weight w/o batteries	270 kg
---------------------------------	--------

PAYLOAD and REQUIREMENTS

Nominal payload 100% deliveries	300 kg
Maximum payload 20% deliveries	350 kg
Center of gravity footprint	L = 600 mm W = 400 mm
Center of gravity height	H = 600 mm

PERFORMANCE

Kinematics and Drive	Differential, bidirectional
Speed	0,1 m/s min 1,0 m/s max
X, Y accuracy	+/- 10 mm
θ accuracy	+/- 1°
Localization rate	5 Hz
Minimum bending radius	0 m; the vehicle turns on its vertical axis
Slope	3% (1,7°)
Slope min bending radius	15 m
Step	±5 mm
Gap	10 mm
Motor wheel power	1x300 W
Braking torque	1x4 Nm

MATERIALS

Wheels coating	Polyurethane grip
Chassis material	AISI 304
Shell material	Painted Steel

BATTERY

Battery	LiFePO4 24V 60 Ah	PureLead 24V 60 Ah
Depth of discharge	70%	40%
Autonomy	6 h	4 h
Recharging time	2 h	3 h
Battery weight	21 kg	38 kg
Battery cycle life	2.000 cycles	1.200 cycles

COMMUNICATION

Communication	WI-FI - WLAN 802.11a/b/g/n - 2,4/5 GHz
---------------	--

SAFETY

Safety devices	<p>Nr. 2 Sick S300 laser scanners Nr. 2 Sick TIM361S laser scanners Sensitive board (front/rear) N.2 E-stop buttons Safety control central unit Sick Flexi</p>
Performance Level	c
Safety field shape	360°

NAVIGATION

Navigation Odometric closed loop via laser scanner (natural navigation)

Mapping Auto acquisition by Mobile Robot

ENVIRONMENT

Temperature from +5 to 35 °C

Working relative humidity from 30% to 80% (absence of condensation)

IP degree 13

REGULATIONS

Regulations

- 2006/42/EC Machinery Directive
- 2014/35/EU Low Voltage Directive
- 2014/30/EU Electromagnetic Compatibility Directive
- ISO 3691-4: 2020 Safety of driverless industrial trucks