

DATASHEET - Epallet 2



DIMENSIONS and WEIGHT

Vehicle size	L = 1.450 mm	
	W = 820 mm	
	H = 490 mm (forks top)	
Equipment	Lift platform c/w pallet forks	
	Plane size	L = 1.120 mm
		W = 575 mm
	Stroke	100 mm
Vehicle weight w/o batteries	313 kg	

PAYLOAD and REQUIREMENTS

Nominal payload 100% deliveries	500 kg
Maximum payload 30% deliveries	700 kg
Payload max size	L = 1.200 mm W = 800 mm H = 1.500 mm
Center of gravity footprint	L = 740 mm W = 512 mm
Center of gravity height	H = 800 mm
Min load frame clearance	W = 720 mm H = 360 mm

PERFORMANCE

Kinematics and Drive	Differential, bidirectional
Speed	0,1 m/s min 1,4 m/s max
X, Y accuracy	+/- 10 mm
θ accuracy	+/- 1°
Localization rate	5 Hz
Minimum bending radius	0 m; the vehicle turns on its vertical axis
Slope	5% (2,9°)
Slope min bending radius	15 m
Step	±5 mm
Gap	15 mm
Motor wheel power	2x1500 W
Braking torque	2x8 Nm

MATERIALS

Wheels coating	Polyurethane grip
Chassis material	AISI 304
Shell material	Painted Steel

BATTERY

Battery	LiFePO4 24V 100 Ah
Depth of discharge	70%
Autonomy	10 h
Recharging time	3 h
Battery weight	38 kg
Battery cycle life	2.000 cycles

COMMUNICATION

Communication	WI-FI - WLAN 802.11a/b/g/n - 2,4/5 GHz
---------------	--

SAFETY

Safety devices	Nr. 2 Sick S300 laser scanners Sensitive board (front/rear) N.2 E-stop buttons Safety control central unit Sick Flexi
Performance Level	d
Safety field shape	360°

NAVIGATION

Navigation	Odometric closed loop via laser scanner (natural navigation)
Mapping	Auto acquisition by Mobile Robot

ENVIRONMENT

Temperature	from +5 to 35 °C
Working relative humidity	from 30% to 80% (absence of condensation)
IP degree	13

REGULATIONS

Regulations	• 2006/42/EC Machinery Directive
	• 2014/35/EU Low Voltage Directive
	• 2014/30/EU Electromagnetic Compatibility Directive
	• ISO 3691-4: 2020 Safety of driverless industrial trucks